

DIMENSIONS

RATED CAPACITY	H	L	W	T
lb/inches				
500-3,000	3.00	2.00	1.11	1/2-20 UNF-2B
5,000	4.00	3.00	1.11	3/4-16 UNF-2B
10,000	4.00	3.00	1.25	3/4-16 UNF-2B
15,000	5.50	4.00	1.25	1-14 UNS-2B
20,000	7.00	5.00	2.00	1 1/4-12 UNF-2B
kg/mm				
300-1,000	76.2	50.8	28.2	M12X1.75
2,000; 3,000	101.6	76.2	28.2	M16X2.00
5,000	101.6	76.2	31.8	M24X2.00
10,000	177.8	125.0	50.8	M30X2.00

SPECIFICATIONS

Full Scale Output	2.0 mV/V ± 1%	Recommended Excitation	10V (15V Maximum)
Zero Balance	± 0.02 mV/V	Insulation Resistance	>2 [50V DC] GΩ
Non-linearity	< ± 0.023%	Compensated Temperature Range	-10°C to 50°C / 14°F to 122°F
Repeatability	< ± 0.030%	Safe Overload	150% of full scale
Hysteresis Error	< ± 0.030%	Breaking Overload	300% of full scale
Creep in 30 min.	< ± 0.030%	Seal Type / IP Rating	Welded Seal / IP68
Input Resistance	400 Ω ± 20	Cable Color Code	Exc+ Red Exc- Black
Output Resistance	350 Ω ± 3		Sig+ Green Sig- White
Element Material	17-4PH Stainless Steel		Shield Bare

PART NUMBER*



Rated Capacity	Deflection (Emax)	Part No.	Weight Approx.
300kg	0.16-0.16mm	101BS-300kg	0.8kg
500kg	0.11-0.21mm	101BS-500kg	0.8kg
1t	0.23-0.33mm	101BS-1t	0.8kg
2t	0.20-0.30mm	101BS-2t	1.5kg
3t	0.30-0.40mm	101BS-3t	1.5kg
5t	0.35-0.45mm	101BS-5t	1.7kg
10t	-	101BS-10t	7.0kg
500lb	0.002-0.006in	101BS-500lb	1.8lb
1Klb	0.004-0.008in	101BS-1Klb	1.8lb
1.5Klb	0.006-0.010in	101BS-1.5Klb	1.8lb
2Klb	0.008-0.012in	101BS-2Klb	1.8lb
2.5Klb	0.010-0.014in	101BS-2.5Klb	1.8lb
3Klb	0.012-0.016in	101BS-3Klb	1.8lb
5Klb	0.009-0.013in	101BS-5Klb	3.3lb
10Klb	0.015-0.019in	101BS-10Klb	3.8lb
15Klb	-	101BS-15Klb	6.4lb
20Klb	0.014-0.018in	101BS-20Klb	15.4lb

* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

INTERCHANGEABLE REFERENCE

Brand	Model
Coti Global	CGSB-SSW
FLINTEC	ULB
HBM	RSC*
Rice Lake	RL20001HE
Vishay Celtron	STC HSS
Vishay Sensortronics	60063
Vishay TedeA-Huntleigh	616*
Vishay TedeA-Huntleigh	620

* Glue Sealed.

 100lb-500lb: up to NTEP 1:4 500 Class III, Single Cell;
 1Klb-20Klb: up to NTEP 1:5 500 Class III, Single Cell
 200kg-1.5t: up to OIML MAA C3, Y=17 000;
 2t-10t: up to OIML MAA C4.5, Y=14 000

For further available P/N's & specifications per NTEP/OIML classes, please contact us.

All product specifications, statements, information and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all conditions. It is the customer's responsibility to validate that a particular product with the properties described in the product specifications is suitable for use in their applications. Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge of product information at the time a publication was made, but are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another manufacturer.

Any use of product outside of specifications or any storage or installation inconsistent with product guidance voids and warranty.

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by ANYLOAD with reference to the use of ANYLOAD's products produces no obligation or liability for the advice given or results obtained.

Although ANYLOAD designs and manufactures its products to the most stringent quality and safety standards, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services or deliverables for use in high risk applications including medical life support, medical device, direct physical patient contact, water treatment, nuclear facilities, weapon systems, mass and air transportation control, flammable environments, or any other potentially life critical uses. Customer understands and agrees that ANYLOAD makes no assurances that the products, services or deliverables are suitable for any high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process. Although all product - related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required. Please contact authorized ANYLOAD personnel to obtain special terms and conditions regarding products designed for such applications or otherwise satisfy specific safety requirements.