


OCSZ Series

FEATURES

- Fast resolution switching
- LED display 5 digits 2.2inch (56mm)
- Fixed hook
- HOLD function
- Tare In / Tare Out
- Unit switch: kg / lb
- Weight accumulation function
- Auto overload alarm at 100%F.S. +9e
- Auto power-off function





Model	ocsz		
Туре	Heavy Duty		
Accuracy Class	Following OIML R76,		
	Class III, NOT certified		
Enclosure	Whole Steel Anti-collision		
Capacity Available	20/30/40/60/100KIb		
Battery Life	>60Hours		
High Quality Load Receptor	Alloy Steel		
Shackle	H.D. Bow		
Hook	H.D. Eye		
High Capacity Rechargeable Battery	Yes 6V/10Ah*		
Infrared Remote Control	Yes		

^{*}With Terminal Top Plate (OCS-6V10Ah-BATCAP)

Rated Capacity	Division	н	H1	L	L1	N.W.	G.W.
20Klb/10t	10lb/5kg	850mm/33.5"	140mm/5.5"	105mm/4.1"	70mm/2.8"	60kg/132lb	72kg/159lb
30Klb/15t	10lb/5kg	900mm/35.4"	160mm/6.3"	140mm/5.5"	75mm/3.0"	80kg/176lb	
40KIb/20t	20lb/10kg	950mm/37.4"	180mm/7.1"	150mm/5.9"	80mm/3.1"	95kg/209lb	
60Klb/30t	20lb/10kg	1120mm/44.1"	215mm/8.5"	165mm/6.5"	90mm/3.5"	165kg/364lb	200kg/441lb
100Klb/50t	50lb/20kg	1350mm/53.1"	235mm/9.3"	180mm/7.1"	105mm/4.1"	395kg/871lb	

^{*}Dimensions and specifications are subject to change without notice.